



Dexter lifts have been manufactured in Finland for almost 40 years

Dexter trailer lifts are suitable for a wide range of applications. The small total weight and large reaches allow it to be used even in demanding places. Four independently adjustable support legs make it easier to level the lift, even on uneven and sloping surfaces. Continuous boom rotation and standard drive provide access to tight spaces. Thanks to the strong and sturdy frame, towing the lift is effortless and the long distances between work sites are not a problem.

All Dexter lifts are made of highstrength steel at our own factory in Nokia and are light but sturdy in relation to their lifting height. The products are designed for demanding operating conditions, with the goal of operational reliability and operational safety in particular. All crane service points are easily accessible and the joints are equipped with lubrication nipples. All components prone to damage are protected by metal guards.



15ZA / 17ZA

The 15ZA and 17ZA articulated telescopic boom lifts offer a wide working range, both in height and sideways, and are suitable for working on building walls, for example. Proportionally adjustable boom control (15ZA as an option) increases working comfort, and the optional petrol engine unit brings electricity where it would not otherwise be available.



MAX WORKING HEIGHT 15ZA: 15,0 m 17ZA: 17.2 m



MAX PLATFORM HEIGHT 15ZA: 13,0 m 17ZA: 15,2 m



OUTREACH 15ZA: 6,5 m / 215 kg, 8,0 m / 120 kg 17ZA: 7,5 m / 215 kg, 9,5 m / 120 kg



WORKING WIDTH 15ZA: 4,3 m 17ZA: 4,6 m



MAX LOAD 215 kg / 2 people



PLATFORM SIZE (I x w x h) 0,8 m x 1,25 m x 1,1 m



PLATFORM ROTATION +/-40°



BOOM ROTATION continuous



PUOMILIIKKEIDEN HALLINTA 15ZA: 2-speed, proportional (optional) 17ZA: proportional



MACHINE LENGTH 15ZA: 6,4 m 17ZA: 6.85 m



MACHINE WIDTH 15ZA: 1,95 m 17ZA: 2,05 m



MACHINE HEIGHT 15ZA: 2,35 m 17ZA: 2,35 m



MACHINE WEIGHT 15ZA: 1 950 kg 17ZA: 2 200 kg



STANDARD POWER SOURCE 15ZA: 230V / 50 Hz / 1,9 kW electric motor 17ZA: 230V / 50 Hz / 1,9 kW electric motor



PETROL ENGINE optional



TRACTION DRIVE standard



GRADEABILITY 15 %



